

Intermec

UP **ollution**
www.upsolutions.com.br

Product Profile



- Rugged design offers years of reliable service
- Choice of Windows® CE or Windows Mobile™ operating system
- Non-volatile storage to protect valuable data
- QVGA display with touchscreen enables both text-based applications and graphical interfaces
- Integrated imaging options
- 802.11b/g radio with choices of wireless security protocols*

CK60 MOBILE COMPUTER

Power, Strength, and Speed: Intermec's CK60 mobile computer provides everything demanded by the tough route environment. Battery capacity to work all day long. Rugged design to provide years of reliable service. Next generation processor and operating system to run complex application software. Non-volatile storage to protect data. CK60 does it all.

Rugged Design: The CK60 utilizes a magnesium top cover and tough rubber bumpers at each corner to achieve extremely rugged environmental specifications. The case is sealed against water and dust to IP64 standards to ensure years of trouble-free service.

Data Storage: Onboard non-volatile memory called Persistent Storage, an exclusive feature of the CK60, preserves applications and databases even if the batteries become depleted. The CK60 also offers an SDIO card slot supporting removable Storage Cards, which allows easy recovery of data from a damaged unit or even more onboard capacity for large databases.

Compatibility & Flexibility: The CK60 is available with either Microsoft® Windows® CE or Microsoft Windows Mobile™ software for Pocket PC. Microsoft

Windows CE provides significant flexibility to those customers who wish to control the user experience; Windows Mobile offers a standard platform which can easily be applied across the enterprise. Both operating systems are supported by advanced software development tools as well as Intermec's Developer Library, providing easy integration of unique hardware capabilities into custom applications.

User Interface: The QVGA resolution display features a touchscreen, allowing the CK60 to run both text-based applications and graphical interfaces. Mobile workers are able to quickly enter large amounts of data using the numeric keypad featuring large, easy-to-use keys and excellent tactile feel. Suitable for both one- and two-handed input, the keypad is designed to last the life of the unit.

Connectivity: The CK60 provides multiple ways in which data may be exchanged between the handheld computer and other devices. High-speed Ethernet, USB Host and Client, and RS232 serial connections are standard on every unit, as is Bluetooth wireless personal area communications. The CK60 may be optionally equipped with a WiFi-certified 802.11b/g radio* for local area wireless communications.

UP **ollution**
www.upsolutions.com.br

Physical Characteristics

Length: 222 mm (8.75 in.)
Width: 90 mm (3.55 in.)
Height at Top/Keypad: 53/36 mm (2.08 in./1.4 in.)
Weight: 704 grams (24.8 oz)

Hardware

Microprocessor: Intel XScale PXA272 Application Processor; 520 MHz
RAM Memory: 64 or 128 MB
Flash ROM: 64 MB
Persistent Store: 128 MB, provides onboard non-volatile storage of applications and data
Removable Storage: SDIO Card Slot, user accessible
Display: Transflective TFT with LED backlight; 3.8" (97 mm) QVGA Color with touch panel
Keypad: 32-key with large numeric keys and LED backlight

Operating System

Microsoft Windows CE 5.0 or Microsoft Windows Mobile Software for Pocket PC*

Software

Development Environments: Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET and C#)
Intermec Developers Library: Integrates with leading development environments; supports device-specific features and bar code scanning
Browser support: IE6 compatible



Barcode Scanning

Option of Integrated 2D Area Imager or Integrated 1D & PDF417 Linear Imager* Supports all popular 1D and 2D symbologies including Code 39, I 2 of 5, S 2 of 5, Matrix 2 of 5, Code 128, Code 93, Code 93i, Codabar, Codablock, MSI, Plessey, UPC, EAN/EAN128, ISBT128, Code 11, RSS, Telepen, PDF417, Micro PDF417, Macro PDF417, Maxicode, Datamatrix, QR Code (2D symbologies require Area Imager)

Standard Communications

USB Host and Client
 Ethernet 10/100 Base-T
 Bluetooth™ Class 1, V2.0 + EDR
 RS232 Serial
 IrDA 1.1

Wireless LAN*

Standards Compliant:
 IEEE 802.11g (2.4 GHz – OFDM)
 IEEE 802.11b (2.4 GHz – DSSS)

Data Rates:

Up to 54 Mbps for 802.11g
 Up to 11 Mbps for 802.11b

Radio Power Output: 50 mW

Security: WEP, WPA, 802.1x (EAP-TLS, TTLS, LEAP, PEAP), 802.11i

Certifications: Wi-Fi, WPA2, Cisco Compatible Extensions V2

Device Management

SmartSystem™ Support: Centralized remote support capability; Configures, updates and maintains single devices or entire populations; Real-time or batch, wired or wireless. Based on Wavelink Avalanche™ with Intermec value added utilities.

Power

Battery Type: Removable, rechargeable Lithium ion; 7.2V, 2400 mAh (17.3 Watt-hours)
Battery Life: Application dependent
Recharging Cycle: 4 hours or less

Environment

Operating Temperature: -4°F to +122°F (-20°C to +50°C)
Storage Temperature: -22°F to +158°F (-30°C to +70°C)
Humidity: 5 to 95%, non-condensing
Electrostatic Discharge: ±8kV Contact Discharge; ±15kV Air Discharge
Rain and Dust Resistance: IP64 compliant
Drop Survival: Multiple 6 ft (1.8 m) drops to steel or concrete

Accessories

Communications and charging dock: Single bay communications dock with USB/Ethernet or USB/modem capabilities and auxiliary battery charger; four-position Ethernet and charge-only multidocks
Serial adapters: Snap-on adapters for USB or RS232 peripherals; snap-on adapter for DEX/UCS connectivity.

Regulatory Approvals

UL and cUL Listed, UL 60950 and UL 1604 and CSA 22.2 No. 157, FCC Part 15, TUV, CE mark

* Future Release



North America
 Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

Systems & Solutions
 550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada
 7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

**Europe/
 Middle East & Africa**
 Headquarters
 Sovereign House
 Vastern Road
 Reading RG1 8BT
 United Kingdom
 tel: 44.118.987.9400
 tel: 44.118.987.9401

Asia
 Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office
 29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86 10.5165.5922
 Fax: 86 10.6567.6778

Australia
 Level 7, 200 Pacific Highway
 Crows Nest, NSW 2065
 Australia
 tel: 61.2.9492.4400
 fax: 61.2.9954.6300

South America & Mexico
 Intermec South America Ltda.
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico
 Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.211.1919
 fax: 525.55.211.8121

Internet
 www.intermec.com

Sales
 800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611602-01A 03/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



Av. Santos Dummont, 1225 - sj. 202 - Santo Antônio - Joinville SC
 CEP: 89218-105 - Fone: 047- 425 - 8312
 www.upsolutions.com.br - comercial@upsolutions.com.br