

Intermec

UPsolution
www.upsolutions.com.br

Product Profile

- Based on industry standard platform Microsoft® Windows® CE .NET
- Powerful Intel® XScale™ processor
- Brilliant backlit ¼ VGA display with pen/touch
- Integrated 1D/2D scanner choices
- High performance 802.11b/g radio with industry security standards
- Advanced ergonomic design for comfort

UPsolution
www.upsolutions.com.br



Cisco
Compatible

CK31 MOBILE COMPUTER

The Intermec® CK31 mobile data collection terminal continues the tradition of delivering on Intermec's promise of rugged, reliable computing, thoughtful ergonomic design and high throughput.

The CK31 delivers the right blend of features and performance with the Microsoft® Windows® CE .NET operating system to provide the optimum combination of real time operation, tools support and standard connectivity.

Intermec has added features that enhance mobile data collection such as simplified setup menus and display icons to provide intuitive, graphic-based status information. Web-based applications can easily be implemented with Microsoft Internet Explorer or Intermec's browsers.

The Intel® XScale™ processor provides more than enough power to drive the bright color display, a range of peripherals, repetitive scanning and wireless network traffic. It delivers the level of response time and throughput required for real time, mission-critical applications in warehousing and distribution or retail (store) operations.

The CK31 screen can be read in a variety of indoor and outdoor conditions. Its full "quarter VGA" resolution features a touch screen, so the CK31 is able to run both

traditional, text-based applications or today's more graphic interface.

A 52 key alphanumeric keyboard provides flexibility for applications that range from shipping and receiving, put-away and picking to cycle counting for the warehouse floor.

The device offers a new area imager for the greatest scanning flexibility by supporting all significant 1D and 2D symbologies. An optional user-installable and removable pistol grip handle is ideal for highly repetitive scanning.

The CK31's Wi-Fi® certified 802.11b/g radio, including compatibility with a Cisco infrastructure, insures the best available wireless network throughput and reliability. A convenient communication dock provides wired host connectivity.

Security features of the CK31 support the highest level of protection. The CK31 complies in full with 802.1x standards including the Windows standard EAP-TLS and PEAP, EAP-TTLS and compatibility with many existing networks with LEAP support.

The CK31 includes a high capacity lithium-ion battery for at least a full shift of usage without having to change the battery.

Intermec

Physical Description

The CK31 is a rugged handheld mobile data collection computer featuring an embedded Microsoft® Windows® CE .NET operating system and an Intel™ XScale™ PXA255 processor.

Physical Characteristics

Length: 233 mm (9.2 in.)
Height: 41 mm (1.6 in.) at grip area
Width at grip: 71 mm (2.8 in.)
Weight: 611 grams (21 oz).
 743 grams (26 oz) with handle.

Hardware

Microprocessor: Intel XScale PXA255, 400 MHz
Memory: 64 MB RAM and 64 MB non-volatile Flash
Memory/Storage extensions: Secure Digital (SD) card slot, user accessible.
Display: 240 x 320 (1/4 VGA) backlit transreflective display with 3.5" diagonal supporting 16-bit color depth (65K colors) and resistive panel touch screen. Integrated stylus storage slot on backside of computer.
Keypad: Bezeled elastomeric keypad with 52-key alphanumeric layout including 4 function (F) keys for one-touch convenience. Options* for 42-key function/numeric and 50-key alphanumeric layouts.
Interfaces: Options* for Bluetooth™† and Ethernet 10/100 base T docking (batch model) USB version 1.1 (through dock) or serial RS-232 (through dock or adapter)

Operating system

Microsoft Windows CE .NET 4.2

Software

Terminal Emulation: VT/ANSI, 5250, 3270. Supports Intermec TE2000 and third party solutions, RDP/Remote Terminal Services
Development Environments: Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET and C#)
Browser support: IE6 and Intermec dcBrowse and iBrowse
Software Development Kit: Supports device-specific features and bar code scanning
Bundled productivity applications: WordPad, Transcriber and Imager scan demo program

Bar Code Scanning**Integrated 1D linear imager:**

Supports all popular symbologies including Code 39, I 2 of 5, S 2 of 5, Matrix 2 of 5, Code 128, Code 93, Code 93i, Codabar, Codablock, MSI, Plessey, UPC, EAN/EAN128, ISBT128, Code 11, RSS, Telepen, PDF417, Micro-PDF417.

Integrated 2D area imager:

Supports all the above plus UCC-EAN Composite, Maxicode, Datamatrix, QR Code. Options** for standard range, long range and advanced long range laser scanners.

Integrated radio

Data Rates: Up to 54 Mbps per 802.11g; 11 Mbps per 802.11b
Antenna: Internal
Standards Compliant: IEEE 802.11g (2.4 GHz - OFDM), IEEE 802.11b (2.4 GHz - DSSS)
Radio Power: 50 mW
Security: WEP, WPA, 802.1x (EAP-TLS, TTLS, LEAP, PEAP), Microsoft VPN*
Certifications: Wi-Fi, WPA
 Cisco Compatible logo indicates compatibility with a Cisco infrastructure

Device Management

SmartSystem™ Support: Centralized remote support capability; Configures, updates and maintains single devices or entire populations; Real-time or batch, wired or wireless; Based on Wavelink Avalanche™ with Intermec's value added utilities

Speaker

Programmable "beeper" with adjustable frequency and duration for scanning feedback or audio indicator under program control

Power

Battery Type: Lithium-Ion 2400 mAh, 7.4V with 10 min. RAM backup (supercap)
Battery Life: 8 or more hours at typical usage level

Environment

Operating Temperature: -20° to 50°C (-4° to 122°F)
Storage Temperature: -20° to 60°C (-4° to 140°F)

Humidity: 10 to 95% non-condensing
Electrostatic Discharge: 6KV contact, 12KV air
Environmental protection: IP64 – completely sealed for dirt and dust, and protected from splashing water and rain.
Drop Survival: Multiple 1.2 m / 4 ft. drops to steel or concrete; limited drops at 1.8m (6ft)
Vibration and shock protection: Tested to MIL-PRF-28800F standards

Accessories

Vehicle mount docks: Powered, non-powered*
Communications and charging docks: Single bay communications cradle with serial/USB/Ethernet, 4-slot communications dock with serial/Ethernet.
Chargers: 4-slot battery charger, 4-slot terminal charge-only dock.
Serial adapters: Snap-on for DB9 printer interface
User Accessories*: Pistol grip handle; holster; hand strap; wrist strap; protective case, protective boot, swiveling belt clip

Regulatory Approvals

UL Listed, UL 60950 and C22.2 No. 60950, TÜV Rheinland GS, EN 60950 and EN 60825-1, Mexico, NYCE Certified NOM 19, FCC Part 15, Canada, ICES-003 Class B, EN 55022 / CISPR 22, Class B, EN 55024. Compliant with all European directives, CE marked.

*Future release

† Bluetooth is a trademark owned by Bluetooth SIG, Inc. USA



Joinville
 Rua Piratuba, 1.707 - Bom Retiro
 CEP 89222-365 – Joinville - SC
 Tel/Fax : 47.3425-8312

SP
 Av. Jabaquara, 1842 Conj. 02 - Sala 2
 Saúde - CEP 04046-300 - Sao Paulo/SP
 Tel: 11.5583.1232

Manaus
 Av. General Rodrigo Otavio, 630 sala 09
 Japim I - CEP 69077-000 – Manaus/AM
 Fone / Fax: 92 3237-2028